

FAREAST 23R

Design Simonis - Voogd

Length (overall) 7.28m

Length 6.97m

Beam 2.55m

Draft Max 1.4m

CONSTRUCTION

HULL

Vacuum infused sandwich hull with isopolyester resin.
White hull.
Powerful inner structure distributes all loads from keel and rigging.

KEEL

1.40m lifting T- shaped keel with carbon fin, lead bulb.

RUDDER

Carbon rudder and tiller, with extension.

DECK

Sandwich build deck with anti-slip surface
Reinforced laminate plates at mounting positions of deck fittings.

INTERIOR

1 PCS Quick-Access utility pockets.

WATER SYSTEM

Manual bilge pump in cockpit.

Loaded displacement 1399 kg

Sail area downwind 80m²

Sail area upwind 31m²

CE certified Class C

MAST & RIGGING

Selden aluminum mast and foot,
1 Set of aft swept spreaders.
Selden boom with outhaul, 1 reefing line Vang system with Harken cleats and blocks.

STANDING RIGGING

Selden S/S standing rigging.
Selden forestay.

RUNNING RIGGING

1 Main halyard
1 Jib halyard
1 Gennaker halyard
1 Cunningham line
1 Outhaul line
2 Jib Sheets
1 Main sheet controls 4:1
Gennaker sheets, blocks, cleats,

J 2.60m

P 8.90m

I 8.82m

E 3.00m

DECK

DECK EQUIPMENT

1 deck organizer
1 set of cleats
2 Jib sheet winches Harken 20.2
2 Jib sheet tracks with cars
Mainsail track with traveler 3:1 and control lines
300mm Pulpits in S/S and stanchions with lifelines
2 ropes and winch store bags
Gennaker drop bag
Companion way cover

SAILS

Red Rum Sails main in black polyester laminate
Red Rum Sails jib in black polyester laminate
Red Rum Sails Gennaker Nylon 0.75 OZ

MISCELLANEOUS

1 winch handle.
Owner's manual.
Outboard engine bracket max 25kg.
Companion way cover.



+27 (0)76 306 4601
+27 (0)83 662 0179



www.performanceyachting.co.za



sales@performanceyachting.co.za

FAREAST 23R

